

RUBRIC ARCTIC 26

High Performance Lubrication

DESCRIPTION

RUBRIC ARCTIC 26 is a high performance hydraulic fluid with a very high viscosity index for all year use in hydraulic equipment operating over a wide temperature range.

ADVANTAGES

- Allows for very good start up performance of hydraulic equipment at very low temperatures
- Good rust and corrosion protection
- Very low pour point
- Zinc-free anti-wear additives for exceptional equipment performance
- Excellent oxidation stability
- Outstanding viscosity control over a wide temperature range

TYPICAL CHARACTERISTICS

Characteristic	Typical Result	Test Method
Viscosity, cSt at 40 °C	26.4	ASTM D445
Viscosity, cSt at 100 °C	8.4	ASTM D445
Viscosity, cSt at - 40 °C	2556	ASTM D445
Viscosity Index	326	ASTM D2270
Density at 20 °C	0.871	ISO 12185
Pour Point, °C	-56	ASTM D97
Flash Point, °C	242	ASTM D92
4 ball wear test, wear scar (1h, 40kg), mm	0.72	ISO 20623
4 ball wear test, weld load, kg	190	ISO 20623

APPLICATIONS

- (Outdoor) hydraulic systems operating under severe conditions including cold start-up and high operating temperatures
- Hydrostatic transmissions and dashpots
- Shock absorbers and motor cycle front forks

SERVICE AND EQUIPMENT

In addition to its product ranges, MotulTech can provide tools and services for the maintenance and in-use monitoring of your lubricants. Please contact your technical sales representative.

IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com